

SHADOW MAX



Reg. No. ECP 02007

Graffiti Solutions

www.graffitisolutions.com

1.800.891.0091

MULTI-SURFACE PERMANENT MARKER REMOVER

GENERAL DESCRIPTION

SHADOW MAX Graffiti Remover is one of five "Graffiti Max" products, each custom formulated for specific graffiti removal needs.

SHADOW MAX is the right choice for the job if you are removing permanent marker from the following "durable non-porous surfaces."

RECOMMENDED FOR REMOVAL ON

Plastics laminates (formica, etc.) fiberglass, playground equipment, white boards, vinyl seats on buses, trains and subway cars.

Porcelain, glazed or ceramic tiles, grout.

Not recommended for use on metal finishes, plexiglass and Lexan.

PRODUCT FEATURES AND BENEFITS

- **Super penetrating** action for maximum wet out or stubborn marks.
- **Fast removals** - maximum wet out and penetrating action gives MAXIMUM removal speeds.
- **Low odor** with minimal or no ventilation requirement for added safety, indoor or out.
- **Nonflammable**, noncombustible, minimal fire hazard formula.
- **All temperature** effective removals from below freezing cold (24°F) to "very hot (90°F+)" conditions.

SAFETY INSTRUCTIONS FOR USE

- **Always wear protective eye wear and chemical resistant gloves. Can cause burns.**
- Protect all exposed skin areas with chemical resistant covering.
- If product gets on skin, wash off immediately. If product gets in eyes, flush with water for 15 minutes.
- Use respirator if sprayed.
- **FOR PROFESSIONAL USE ONLY.**

GENERAL INSTRUCTIONS FOR USE

- Wear rubber gloves.
- Use hand trigger sprayer.
- Spray **SHADOW MAX** directly on affected area or on to a soft dry clean cloth.
- Wipe cloth over affected area. A nonabrasive form of gentle agitation may also be used such as a looped Teflon pad.
- Allow one minute working time.
- Wipe graffiti off with a damp clean cloth.
- Repeat process if necessary.
- Wipe off area with wet cloth to neutralize chemical and stop cleaning action.
- Finish by wiping affected area with a clean dry cloth.
- Clean up all equipment after each use with water.

SPEC'S - GENERAL PROPERTIES

CONSISTENCY

Thin liquid with maximum wetting and penetrating action.

COVERAGE

200 to 400 sq. ft/gal. depending on porosity of surface.

TEMPERATURE USAGE

Not limited, will work slower at cold temperatures.

STORAGE

Stores between 40°F and 130°F. DO NOT FREEZE. If frozen, thaw and remix before using. Keep out of the reach of children.

FLAMMABILITY

Nonflammable, noncombustible. Flash point over 200°F.

V.O.C.S

.4 lbs/gallon, 50 grams/liter.
H.A.P.S. - none.

BIODEGRADABLE

Yes

VOLATILITY

Very low rate of evaporation. Ventilation required in confined areas. Respirator if sprayed.

SHIPPING

Not regulated, D.O.T. Proper shipping name: Cleaning Compound N.O.S., Class 55.

EFFECTIVE ON THE FOLLOWING

Plastic laminates (formica, etc.) fiberglass, playground equipment, white boards, vinyl seats on buses, trains and subway cars.

TEST FIRST

SHADOW MAX should not be used for any other purpose/removal, without thoroughly testing in an inconspicuous area for effect.

NOTE: For removals from all types of metals, "durable" baked on painted surfaces such as auto, bus, truck, other factory applied paints, Fiberglass, traffic or reflective signs, use our **SMOOTH MAX** Graffiti Remover.