

SMOOTH MAX



Reg. No. ECP 02007

Graffiti Solutions

www.graffitisolutions.com

1.800.891.0091

G R A F F I T I R E M O V E R

GENERAL DESCRIPTION

SMOOTH MAX Graffiti Remover is one of five "Graffiti Max" products, each custom formulated for specific graffiti removal needs.

SMOOTH MAX Graffiti Remover is the right choice for the job if it is a "smooth and durable surface" such as the following.

RECOMMENDED FOR REMOVAL ON

METALS: Stainless steel, galvanized, aluminum, brass, copper, anodized aluminum and zinc.

GLASS: All types - glazed tiles, ceramic, porcelain, polished stone.

DURABLE PAINTED: Factory applied baked on or catalyzed paint such as auto, truck, bus, utility boxes, railcars or similar.

DURABLE PLASTICS: Fiberglass, polyethylene or polypropylene portable toilets or bathroom partitions, laminated wood, plexiglas, Lexan and vinyl siding.

PRODUCT FEATURES AND BENEFITS

- **Thick Gel** clings to surfaces without messy drips and runs.
- **Fast removals** - just a few minutes for most uses.
- **Low odor** with minimal or no ventilation requirement for added safety, indoor or out.
- **Nonflammable**, noncombustible, for added safety in use.
- **All temperature** effective removals from freezing cold to "very hot" conditions.

SAFETY INSTRUCTIONS FOR USE

- **Always wear protective eye wear and chemical resistant gloves during handling and use.**
- Protect all exposed skin areas with chemical resistant covering.
- If product gets on skin, wash off immediately. If product gets in eyes, flush with water for 15 minutes.
- **FOR PROFESSIONAL USE ONLY.**

GENERAL INSTRUCTIONS FOR USE

- **SHAKE BEFORE USE.**
- Should be tested first in an inconspicuous area for effect on any painted or plastic surface.
- Apply by spray, brush, roller or pump sprayer.
- Allow to penetrate marks for several minutes (30-40 minutes cold temperatures).
- Use gentle agitation with stiff brush or looped Teflon pad.
- Remove with a clean dry cloth or rinse off with water hose or pressure washer.
- Use water rinse or soap and water followed by water rinse for cleaning equipment.
- Repeat process if necessary.

SPEC'S - GENERAL PROPERTIES

CONSISTENCY

Thick gel clings to vertical surfaces without dripping.

COVERAGE

Non-porous surfaces 200 to 300 sq. ft/gal.

TEMPERATURE USAGE

Not limited, will work slower at cold temperatures.

STORAGE

Stores between 40°F and 130°F. DO NOT FREEZE. If frozen, thaw and remix before using. Keep out of the reach of children.

FLAMMABILITY

Nonflammable, noncombustible. Flash point over 200°F.

V.O.C.S

.2 lbs/gallon, 25 grams/liter.
H.A.P.S. - none.

BIODEGRADABLE

Yes

VOLATILITY

Very low rate of evaporation. No ventilation required unless used in a confined space.

SHIPPING

Not regulated, D.O.T. Proper shipping name: Cleaning Compound N.O.S., Class 55.

EFFECTIVE ON THE FOLLOWING

Spray paint graffiti, marker, pen, ink crayon, shoe polish, lipstick, pencil, decals, and stickers, and most other graffiti marks or stains. Removes road tar, asphalt, wax, tree sap and many other difficult to remove graffiti from durable smooth surfaces.

TEST FIRST

SMOOTH MAX should not be used for any other purpose/removal, without thoroughly testing in an inconspicuous area for effect.

EQUIPMENT/TOOL CLEANUPS

Dried paints, adhesives, caulking materials on equipment, floors, tools, brushes, rollers, paint spills or over sprays can be effectively removed with **SMOOTH MAX** Graffiti Remover.

NOTE: If removing graffiti or shadows from porous surfaces such as brick, cement, grout etc. We recommend using our **ELEPHANT SNOT**® Graffiti Remover or **SHADOW MAX** for shadow removals.